

Load Break Switches Sirco M

3P from 16 to 80A



2205

Product
Family

3

Number of
Pole

000

Rated
Current

Type		Load Break Switches	
		Sirco M [2205]	
Switching mode		Toggle switch	
Number of pole		3P	
Rated current		16, 20, 25, 32, 40A	63, 80A
Rated operating voltage [Ue]		400..690VAC	
Rate short circuit		50 kA	
Interlock able		Yes	
Operating cycles		100000	
Standard		IEC 60947-3, UL 508, UL98 GB/T14048-3	
Terminal	Connection	Cable end 0.5 ... 16mm ²	Cable end 2.5 ... 35mm ²
	Torque N.m	2.2 N.m	3.85 N.m
Mount		DIN rail, panel or modular panel	
External operation		Front, left side or right side	
Degree of protection		IP20	
Dimension			

Load Break Switches Sirco M

3P from 16 to 80A



22053000



22001000

Load Break Switches Sirco M Toggle 3P From 16A to 80A

Pole	Type	Rating In (A)	Reference
3P	M1	16 A	22053000
	M1	20 A	22053001
	M1	25 A	22053002
	M1	32 A	22053003
	M1	40 A	22053004
	M2	63 A	22053006
	M2	80 A	22053008
Additional Poles			
1P	M1	16 A	22001000
	M1	20 A	22001001
	M1	25 A	22001002
	M1	32 A	22001003
	M1	40 A	22001004
	M2	63 A	22001006
	M2	80 A	22001008
	M3	100 A	22001010
	M3	125 A	22001011
Additional Protective Neutral Poles			
1P	M1	16...40 A	22005005
	M2	63...80 A	22005009
	M3	100...125 A	22005011
Additional Protective Earth Poles			
1P	M1	16...40 A	22009005
	M2	63...80 A	22009009
	M3	100...125 A	22009011

*For any special accessory such as extension shafts or enclosed solutions, please consult us for more details.

** Add one or two additional poles and transform :

- 3 poles SIRCO M into a 4 poles

- 6 poles SIRCO M into a 8 poles

***Additional poles can be mounted directly on either the left or the right side of the switch.