

Load Break Switches Sirco

3P, 4P from 1250 to 3200A



2600

Product
Family

3

Number of
Pole

121

Rated
Current

Type		Load Break Switches	
		Sirco [2600]	
Switching type		Direct handle / External	
Number of pole		3P, 4P	
Rated current		1250, 1600, 1800A	2000, 2500, 3200A
Rated voltage [Ue]		415 VAC	
Operating handle		Front operation	
Rated operating voltage[V]		400~500	
Operating cycles		4000	3000
Standard		IEC 60947-3	
Terminal	Connection	Busbar 100mm	
	Torque N.m	45 N.m	
Mount		Back plate mounting	
Interlock able		Yes	
Degree of protection		IP20	
Dimension			

Load Break Switches Sirco

3P, 4P from 1250 to 3200A



26003121



26004121

Load Break Switches Sirco 3P, 4P From 1250A to 3200A

Pole	Rating In (A)	Reference	
		Direct Handle	Body
3P	1250 A	27997012	26003121
	1600 A	27997012	26003161
	1800 A	27997012	26003181
	2000 A	27997012	26003200
	2500 A	27997012	26003250
	3200 A	27997012	26003320
4P	1250 A	27997012	26004121
	1600 A	27997012	26004161
	1800 A	27997012	26004181
	2000 A	27997012	26004200
	2500 A	27997012	26004250
	3200 A	27997012	26004320