

Motorised Changeover Switches ATyS r, ATyS d

4P from 1600 to 3200A



9523

Product
Family

4

Number of
Pole

200

Rated
Current

Type		Motorised Changeover Switches		
		ATyS r [9523]		ATyS d [9533]
Switching mode		Auto , manual mode selector switch		
Number of pole		4P		
Rated current		1600A	2000, 2500, 3200A	2000, 2500, 3200A
Auxiliary power supply		230VAC (208 - 277Vac ± 20%)		2 x 230VAC (208 - 277Vac ± 20%)
Operating handle		I-O-II		
Interlock able		Yes		
Operating cycles		3000		
Standard		IEC 60947-6-1, IEC 60947-3 GB/T14048-11		
Terminal	Connection	Busbar 90mm		
	Torque N.m	45 N.m		
Mount		Back plate mounting		
Rated operating voltage		400~690VAC		
Degree of protection		IP20		
Dimension				

Motorised Changeover Switches ATyS r, ATyS d

4P from 1600 to 3200A



95234--



95334--

Motorised Changeover Switches ATyS r 4P from 1600A to 3200A

Pole	Description	Rating (A)	Reference
4P	Motorized Transfer Switch	ATyS r 1600A	95234160
	Motorized Transfer Switch	ATyS r 2000A	95234200
	Motorized Transfer Switch	ATyS r 2500A	95234250
	Motorized Transfer Switch	ATyS r 3200A	95234320

Motorised Changeover Switches ATyS d 4P from 2000A to 3200A

Pole	Description	Rating (A)	Reference
4P	Motorized Transfer Switch	ATyS d 2000A	95334200
	Motorized Transfer Switch	ATyS d 2500A	95334250
	Motorized Transfer Switch	ATyS d 3200A	95334320