




EDS	DH	100VA	220	24V
Range Name	Product name	Capacity	Voltage Primary	Voltage Secondary

Type		Transformer																	
		DH																	
Capacity power (VA)		50	100	150	200	250	300	350	400	450	500	550	600	700	800	1000			
Static Current (mA)		10	15	20	30	35	40	45	50	55			60			65	75		
Efficiency (%)		90	92	93	94			95											
Voltage Primary (V)		220,230, 440 VAC																	
Voltage Secondary (V)		12, 24, 230 VAC																	
Rated Frequency		50/60Hz																	
Output current (A)		Capacity power (VA) / Voltage Secondary (V)																	
Standard		IEC61588, BS3535, UL1411																	
Dimension	Height (mm)	45	50	55	60	65	60	65	72	70	80	70	85	85	85	90			
	Diameter (mm)	100	105	120	125	135			140			145	150	155	160	180			
Mount		Mounting plate fixed																	
Insulation		High Grade PVC Taping																	
Terminal		Wire leads connection																	
Dimension																			

Power Supply Transformer DH Series



Input	Output	Dimensions H x Ø (mm)	Capacity Power	Efficiency %	Reference
220 VAC	24 VAC	50x105	100 VA	0.92	EDSDH100VA220i24V
220 VAC	24 VAC	60x125	200 VA	0.94	EDSDH200VA220i24V
220 VAC	24 VAC	60x135	300 VA	0.94	EDSDH300VA220i24V
220 VAC	24 VAC	75x140	400 VA	0.95	EDSDH400VA220i24V
220 VAC	24 VAC	85x150	600 VA	0.95	EDSDH600VA220i24V
400 VAC	220 VAC	85x160	800 VA	0.95	EDSDH800VA400i230V

Other transformers are available on request, please consult us