

Thermal Overload Relay MT Type

3P from 65A to 800A



MT

225

08000A

3H

Range
Name

Amp
Frame

Rated
Current

Number of
Heater

Type	Thermal Overload Relay MT Type		
	MT-225	MT-400	MT-800
Number of pole	3P		
Rated current	80 to 200A	107A to 350A	265A to 660A
Setting range (A)	65A to 240A	85A to 400A	200A to 800A
Type	Non-differential(3P-3 heater) [3H]		
Auxiliary contact	1NO+1NC		
Standard	IEC/EN 60947-1, IEC/EN 60947-4-1		
Rated voltage [Ue]	690VAC		
Rated impulse voltage [Uimp]	6kV		
Terminal	Upstream	Lug clamp	
	Downstream	Lug clamp	
Applied contactors	MC-185a, 225a	MC-265a, MC330a, 400a	MC-500a, MC-630a, MC-800a
Size (H,W,D)	141x147x184 mm	171x151x198 mm	530x306x230 mm
Mounting position	Vertical plane		
Dimension			

Thermal Overload Relay MT Type

3P from 65A to 800A



MT225



MT400



MT800

Thermal Overload Relay MT Type 3P from 65A to 800A

Relay Setting Range (A)	Type	Reference
Applied Contactor MC-185a, 225a		
120~185	MT225	MT22515300A3H
160~240	MT225	MT22520000A3H
Applied Contactor MC-265a, 330a, 400a		
200~330	MT400	MT40026500A3H
260~400	MT400	MT40035000A3H
Applied Contactor MC-500a, 630a, 800a		
400~630	MT800	MT80051500A3H
520~800	MT800	MT80066000A3H